



**Zebra Technologies Europe Limited**  
**Zweigniederlassung Deutschland**  
**Birkenwaldstr. 38**  
**63179 Obertshausen**  
**Germany**  
**Tel.: +49 61 04 / 70 99 0**  
**Fax: +49 61 04 / 70 99 22**  
**eMail: germany@zebra.com**



## IPDS-Ethernet-Box for Zebra Printers

With the EBox, CSP GmbH introduces a new external IPDS interface for all Zebra Printers with ZPL and EPL emulations. This makes possible the printing of IPDS data, enabling users to operate the IPDS printer precisely for Zebra applications providing more flexibility in many environments.

|                                       | <b>CSP EBox ZPL</b>  | <b>CSP EBox EPL</b>                             |
|---------------------------------------|--|---|
| AS/400 / iSeries supported protocols: | TCP/IP (PPR/PPD)   | TCP/IP (PPR/PPD)                                |
| LAN supported protocols:              | TCP/IP (LPR/LPD, RAW), IPX/SPX, NetBIOS over IP            | TCP/IP (LPR/LPD, RAW), IPX/SPX, NetBIOS over IP |
| Ethernet                              | 10/100BaseT  | 10/100BaseT                                     |
| IPDS Twinax Emulation                 | IBM 3812-2, 4028, 4312                                     | IBM 3812-2, 4028, 4312                          |
| Printers supported                    | All Zebra Printers with ZPL/2 Emulation <b>and</b> 203 dpi | ELTRON 2742, 2746<br>GENICOM 6342, 6441         |
| Printer port                          | IEEE 1284  | IEEE 1284                                       |
| Printer status                        | Full report back to AS/400                                 | Full report back to AS/400                      |
| OS/400 release                        | V3R7 or later  | V3R7 or later                                   |
| IPDS towers                           | All Towers supported except LF (Loaded Fonts)              | All Towers supported except LF (Loaded Fonts)   |
| Configuration                         | Control panel or Internet browser                          | Control panel or Internet browser               |
| Power supply                          | External 12V 800 mA  | External 12V 800 mA                             |
| LCD display                           | 2 line English or German language                          | 2 line English or German language               |
|                                       |  |   |



# CSP

Computer  
 Schnittstellen  
 Peripherie GmbH  
 Justus-von-Liebig-Str. 5  
 63110 Rodgau  
 Tel.: 06106 84070  
 Fax: 06106 61560

